

COMMON SIZES and API STANDARDS / NOT SCHEDULED

NPS	OD	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	WT	lbs/ft	
3"	3.500	0.125	4.51	0.156	5.58	0.188	6.66	0.250	8.69	0.281	9.67															
3 1/2"	4.000	0.125	5.18	0.156	6.41	0.188	7.66	0.250	10.02	0.281	11.17															
4"	4.500	0.125	5.85	0.156	7.24	0.188	8.67	0.219	10.02	0.250	11.36	0.281	12.67	0.312	13.97											
5"	5.563	0.156	9.02	0.188	10.80	0.219	12.51	0.244	13.87	0.275	15.55	0.281	15.87	0.312	17.51	0.344	19.19									
6"	6.625	0.109	7.59	0.125	8.69	0.134	9.30	0.156	10.79	0.188	12.94	0.219	15.00	0.250	17.04	0.312	21.06	0.344	23.10	0.375	25.05					
8"	8.625	0.105	9.56	0.134	12.16	0.172	15.54	0.188	16.96	0.203	18.28	0.219	19.68	0.264	23.60	0.312	27.73	0.344	30.45	0.375	33.07	0.438	38.33			
10"	10.750	0.105	11.95	0.134	15.21	0.188	21.23	0.203	22.89	0.219	24.65	0.279	31.23	0.344	38.27	0.438	48.28									
12"	12.750	0.105	14.19	0.134	18.07	0.188	25.25	0.203	27.23	0.219	29.34	0.281	37.46	0.312	41.48	0.344	45.62	0.438	57.65							
14"	14.000	0.105	15.60	0.134	19.86	0.188	27.76	0.203	29.94	0.219	32.26	0.281	41.21	0.344	50.22	0.469	67.84	2.000	256.56	2.125	269.76	2.200	277.51	2.500	307.34	
16"	16.000	0.134	22.73	0.188	31.78	0.203	34.28	0.219	36.95	0.281	47.22	0.344	57.57	0.406	67.68	0.438	72.86	0.469	77.87							
18"	18.000	0.188	35.80	0.203	38.62	0.250	47.44	0.281	53.23	0.344	64.93	0.406	76.36	0.469	87.89											
20"	20.000	0.250	52.78	0.281	59.23	0.312	65.66	0.344	72.28	0.406	85.04	0.438	91.59	0.469	97.92											
22"	22.000	0.281	65.24	0.312	72.34	0.344	79.64	0.406	93.72	0.438	100.96	0.469	107.95	0.625	142.81											
24"	24.000	0.281	71.25	0.312	79.01	0.344	86.99	0.406	102.40	0.438	110.32	0.469	117.98													
26"	26.000	0.250	68.82	0.281	77.26	0.344	94.35	0.406	111.08	0.438	119.69	0.469	128.00	0.562	152.83											
28"	28.000	0.250	74.16	0.281	83.26	0.344	101.70	0.406	119.76	0.438	129.05	0.469	138.03													
30"	30.000	0.250	79.51	0.281	89.27	0.344	109.06	0.406	128.44	0.438	138.42	0.469	148.06													
32"	32.000	0.250	84.85	0.281	95.28	0.344	116.41	0.406	137.12	0.438	147.78	0.469	158.08													
34"	34.000	0.250	90.20	0.281	101.29	0.344	123.77	0.406	145.80	0.438	157.14	0.469	168.11													
36"	36.000	0.250	95.54	0.281	107.30	0.344	131.12	0.406	154.48	0.438	166.51	0.469	178.14	0.562	212.90											
42"	42.000	0.250	111.58	0.375	166.86	0.500	221.82																			
48"	48.000	0.250	127.61	0.375	190.92	0.500	253.89																			

Any size not listed can be calculated by the following formula to obtain weight per foot.

$$(OD - WT) \times WT \times 10.69 = \text{Weight Per Foot}$$

Example: 3 1/2" OD with 0.216 WT -- $(3.500 - 0.216) \times 0.216 \times 10.69 = 7.582$ Pounds Per Foot