

EXPANDED METAL

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Size of Strands in Inches		
		Plain	Width	Length	Width	Length	Width	Length
1/2" - 13	1.47		5/16	15/16	.500	1.2	.092	.096
3/4" - 16 Hy	.54		13/16	1 3/4	.923	2.0	.060	.101
3/4" - 13	.80		3/4	1 11/16	.923	2.0	.092	.096
3/4" - 9	1.80		11/16	1 9/16	.923	2.0	.134	.150
1 1/2" - 9	1.20	1	1/8	2 3/8	1.330	3.0	.134	.144
1 1/2" - 6	2.50	1		2 5/16	1.330	3.0	.198	.203

FLATTENED EXPANDED METAL

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Approximate Thickness of Strands in Inches	
		Plain	Width	Length	Width		Length
1/4"-18 - 20	1.11		3/32	11/16	.255	1.031	.040
1/2"-18 - 20	.66		9/32	1	.500	1.260	.039
1/2"-16 - 18	.82		1/4	1	.500	1.260	.050
1/2"-13 - 15	1.40		1/4	1	.500	1.260	.070
3/4"-16 - 18 Hy	.51		3/4	1 3/4	.923	2.100	.048
3/4"-13 - 15	.75		11/16	1 25/32	.923	2.100	.070
3/4"- 9 - 11	1.71		9/16	1 11/16	.923	2.120	.120
1 1/2"-13 - 15	.57	1	1/16	2 3/4	1.330	3.200	.070
1 1/2"- 9 - 11	1.14	1		2 9/16	1.330	3.200	.110

WALKWAY, SKYWALK and GRATINGS

Style Designation	Lbs./ Sq. Ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Size of Strands in Inches		
		Plain	Width	Length	Width	Length	Thick	Width
Walkway	4.27	1		2 7/8	1.412	4.00	.250	.300
Skywalk	3.14	1	5/8	4 7/8	2.000	6.00	.250	.312
3.0 lb. Grating	3.00		15/16	3 7/16	1.333	5.33	.183	.264
4.0 lb. Grating	4.00		15/16	3 7/16	1.333	5.33	.215	.300

All dimensions and weights are approximate and are subject to mill tolerances.