

HOT ROLLED ROUNDS
A-36

Size	Lbs./Ft.	Lbs./20'
1/4	0.17	3.34
5/16	0.26	5.22
3/8	0.38	7.52
7/16	0.51	10.22
1/2	0.67	13.36
3/8	0.85	16.90
5/8	1.04	20.86
3/4	1.50	30.04
7/8	2.05	40.90
1	2.67	53.40
1 1/8	3.38	67.60
1 1/4	4.17	83.44
1 3/8	5.05	100.98
1 1/2	6.01	120.16
1 3/4	8.18	163.60
2	10.68	213.60
2 1/2	16.69	333.80

COLD DRAWN ROUNDS
C1018, C1045, C1144SR and Stress Relieved

Size	Lbs./Ft.	Lbs./20'		Size	Lbs./Ft.	Lbs./20'
13/16	1.76	35.20		2 7/8	15.87	317.40
7/8	2.04	40.80		2 1/2	16.69	333.80
15/16	2.35	47.00		2 5/8	18.40	368.00
1	2.67	53.40		2 11/16	19.29	385.80
1 1/16	3.02	60.40		2 3/4	20.19	403.80
1 1/8	3.38	67.60		2 7/8	22.07	441.40
1 3/16	3.77	75.40		2 15/16	23.04	460.80
1 1/4	4.17	83.40		3	24.03	480.60
1 5/16	4.60	92.00		3 3/16	27.13	542.60
2 3/5	5.05	101.00		3 7/16	31.55	631.00
1 7/16	5.52	110.40		3 1/2	32.71	654.20
1 1/2	6.01	120.20		3 11/16	36.31	726.20
1 9/16	6.52	130.40		3 15/16	41.40	828.00
1 5/8	7.05	141.00		4	42.73	854.60
1 11/16	7.60	152.00		4 3/16	46.83	936.60
1 3/4	8.18	163.60		4 1/4	48.23	964.60
1 13/16	8.77	175.40		4 5/16	49.66	993.20
1 7/8	9.39	187.80		4 7/16	52.58	1051.60
1 15/16	10.02	200.40		4 1/2	54.08	1081.60
2	10.68	213.60		4 15/16	65.10	1302.00
2 1/16	11.36	227.20		5	66.76	1335.20
2 1/8	12.06	241.20		5 1/2	80.78	1615.60
2 3/16	12.78	255.60		6	96.13	1922.60
2 1/4	13.52	270.40		6 1/2	112.82	2256.40
2 3/8	15.06	301.20				